

FIG. 1





FIG. 2



00000T" 58T86960




[illegible]

FIG. 4


FOURTH STEP



FIFTH STEP



SIXTH STEP



TO SEVENTH STEP

09698185 103000

FIG. 5




FIG. 6




FIG. 7






FIG. 8



[illegible]

**000000000000**




FIG. 11




FIG. 12




FIG. 13




FIG. 14








FIG. 15



00000T" 58T86960

FIG. 16



00000T" 58T86960

FIG. 17




FIG. 18




FIG. 19





FIG. 20



0916918185 103000

FIG. 21




FIG. 22




FIG. 23




FIG. 24






FIG. 25



**00000000000000000000**



**00000000000000000000**




FIG. 27







FIG. 28



000001"58T86960

FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33a





FIG. 33b



00000T" S8T86960

FIG. 34a




FIG. 34b





FIG. 35



09698185-103000

FIG. 36




FIG. 37




FIG. 38




FIG. 39a




FIG. 39b





FIG. 39c



00000T"58T86960



000001"58T86960

FIG. 40





FIG. 41



PHYSICAL VALUES AND SPUTTER RESISTANCE OF  
STRESS RELAXATION LAYER CANDIDATE MATERIAL  
(X: OCCURRENCE OF CRACKS,  $\Delta$ : OCCURRENCE OF WRINKLE,  
O: NO ABNORMALITY)